#### IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Express Mail No.: EL627426544US In re Application of: TAKALO et al.

FILING DATE: Herewith ART UNIT:

TITLE: A METHOD FOR IMPLEMENTING A TRANSCEIVER AND A

TRANSCEIVER

ATTORNEY DOCKET NO.: 460-010353-US(PAR)

The Commissioner of Patents and Trademarks Washington, D.C. 20231

### PRELIMINARY AMENDMENT

Dear Sir

Please amend the above-identified, enclosed patent application as follows:

#### IN THE CLAIMS

Please amend the claims 3, 5, 11 and 13 as rewritten below:

- The method according to claim 1, characterized in that at the receiving stage, also at least a first conversion step is taken, in which the received analog signal is converted to digital form.
- 5. The method according to claim 3, characterized in that at the receiving stage, before the first filtering step, at least a first mixing step is taken, in which the received radio-frequency signal is mixed with a local oscillator signal.
- 11. The transceiver (1) according to claim 9, **characterized** in that it also comprises means (AD1, AD2) for converting the received analog signal to digital form.
- 13. The transceiver (1) according to claim 11, characterized in that it also comprises at least one mixer (M1, M2) to mix a local oscillator signal with the received radio-frequency signal.

## REMARKS

In accordance with 37 C.F.R. §1.121 (as amended on 11/7/2000) the rewritten claim(s) above are shown on separate page(s) marked up to show all the changes relative to the previous version of that section.

Respectfully submitted,

Clarence A. Green, Reg. No.: 24,622

Perman & Green, LLP

425 Post Road

Fairfield, CT 06430

(203) 259-1800

Customer No.: 2512

# Application entitled: A METHOD FOR IMPLEMENTING A TRANSCEIVER AND A TRANSCEIVER

## MARKED UP CLAIM(S)

- The method according to claim 1-or-2, characterized in that at the receiving stage, also at least a first conversion step is taken, in which the received analog signal is converted to digital form.
- 5. The method according to claim 3-or-4, characterized in that at the receiving stage, before the first filtering step, at least a first mixing step is taken, in which the received radio-frequency signal is mixed with a local oscillator signal.
- 11. The transceiver (1) according to claim 9-or-10, characterized in that it also comprises means (AD1, AD2) for converting the received analog signal to digital form.
- 13. The transceiver (1) according to claim 11-or-12, characterized in that it also comprises at least one mixer (M1, M2) to mix a local oscillator signal with the received radio-frequency signal.